



ELITE and DUO-150 Comparison Chart

ENDURA Li-ion V-Mount Battery Comparison



Model	ELITE	DUO-150
Capacity	136Wh (14.8V, 9.2Ah)	146Wh (14.8V, 9.8Ah)
Max Voltage	16.8V	16.8V
Max Discharge	110W/9.2A	120W/10A
End Voltage	12V	12V
Protocol	BMS & SMBus	SMBus
Battery Weight	2.76lbs.	2.31lbs.
Battery Dimensions	3.94 x 6.69 x 2.76"	3.82 x 5.75 x 2.32"
Removable Cartridges	Yes (model PC-14)	No
Capacity Display	5 LED (10 Step)	5 LED (6 Step)
D-Tap Power Output	No	Yes x 2
USB Power Output	No	Yes
30W Load Runtime*	4.5 hours	4.8 hours
60W Load Runtime*	2.26 hours	2.4 hours
80W Load Runtime*	1.7 hours	1.8 hours

All batteries have built-in over-charge, over-discharge, over-current, and temperature protection circuitry.

*Run times are approximate and are based on new battery packs

All ENDURA batteries are compatible with ENDURA Chargers



VAL-4Si



VL-4Si



VL-4S



VL-2SPlus



VL-2Plus



VL-PVC1

IDX System Technology, Inc.
 19001 Harborage Way, Suite 105
 Torrance, CA 90501
 U.S.A.
 Telephone: (310) 328-2850
 Fax: (310) 328-8202



For further information, email us: idx.usa@idx.tv or visit our website www.idxtek.com
 IDX reserves the right to change the specifications contained herein without notice.

07192013