



**A-E2XL1 V-Mount Camera Plate
for Canon XL1 Digital Video Camcorder**

This adaptor plate is exclusively designed for use of ENDURA lithium-Ion batteries with the Canon XL1 Digital Video Camcorder.

Features: The A-E2XL1 is a V-Mount adapter plate that allows direct connection of ENDURA batteries. Where compatible, two ENDURA batteries can be 'PowerLinked' to increase run times.

: (Lighting) It is recommended that an IDX, *X-Lite II 12V professional ENG on-camera light is used. This can be powered via the D-Tap connector, found on the A-E2XL1.

**When powering the X-Lite II and camera together it is recommended that a 20~35W bulb is used and that the ENDURA batteries are used in the 'PowerLink' mode.*

: (Wireless Receiver) The following wireless receiver fittings are available as optional accessories O-LWP(F) / O-LWR(B).

Specifications : Output : 7.2V/max. 2A
: DC-Out : 14.4V (Direct voltage of ENDURA batteries)
: Dimensions : 96(W)x172(H)x58(D)mm
: Weight : Approx 310g

Applicable Batteries

All ENDURA lithium ion batteries (E-50 / E-50S / E-80 / E-80S)

Operating Precaution

To use with lighting applications, the maximum discharge current when two E-50 are PowerLinked is 8A (maximum 4A per battery). Over 8A of load may activate battery protection circuit and automatically stop supply of power (two E-80 PowerLinked max 12A maximum per battery 6A).