



SD-1E

ENDURA POWER BELT /
DV ADAPTOR

SPECIFICATIONS

- DC output : 1 channel (4 pin XLB2 connector)
- Output voltage : 12~14.4V Pin No's : 1 minus / 4 plus
: 7.2V Pin No's : 2 plus / 3 minus
- Discharge current : 12~14.4V Maximum 6.5A
: 7.2V Maximum 2A
- Number of batteries to be used : Maximum 2 (2 in PowerLink mode)
- Dimensions : 67.5(W) x 106(H) x 34.5(D) mm approx
: 2.66(W) x 4.17(H) x 1.36(D) inches approx
- Weight : Approx. 0.62 lbs.

APPLICABLE BATTERIES

- E-50, E-80, E-50S, E-80S

CAUTION

- Maximum discharge current when using 7.2V output voltage is **2A**.
- When powering 7.2V equipment be sure to follow XLR wiring instruction
i.e. For 7.2V Output Pin No's : 2 = Plus & 3 = Minus

In Japan/Asia

IDX COMPANY LTD.
6-28-11 Shukugawara,
Tama-ku, Kawasaki-Shi,
Kanagawa-ken 214-0021,
Japan

Sales and service

Phone +81-44-850-8801
Fax +81-44-850-8838
E-mail idxjapan@idx.tv

In the United States

IDX System Technology
1602 Lockness Place,
Torrance, CA 90501 USA

Sales and Service

Phone +1-310-891-2800
Fax +1-310-891-3600

E-mail idxusa@idx.tv

In Europe/Middle East

IDX Technology Europe Ltd.
Unit 34 Metropolitan Centre,
3 Taunton Road, Greenford,
Middlesex UB6 8UQ, England

Sales and service

Phone +44-20-8813-1666
Fax +44-20-8813-1777

E-mail idxeurope@idx.tv