



## CW-1 Power Options

Wireless HDMI Type Video Transmission System Power Options

### A-CWJ-TX

Battery Adapter for CW-1 TX (Transmitter)

#### Features

- Designed to be used with SSL-JVC50 battery
- 5VDC output from USB connector
- Comes with camera shoe adapter
- Bracket to secure CW-1 TX
- 1/4-20 screw hole on bottom

#### Technical Specifications

Output Voltage: 5VDC

Input Voltage: 6.5V-9VDC

Dimensions: 4.41 (W) x 2.84 (H) x 3.51 (D) inches

Weight: Approx. 8.8 oz



### A-CWJ-RX

Battery Adapter for CW-1 RX (Receiver)

#### Features

- Designed to be used with SSL-JVC50 battery
- 5VDC output from USB connector
- 1/4-20 screw hole on bottom

#### Technical Specifications

Output Voltage: 5VDC

Input Voltage: 6.5V-9VDC

Dimensions: 4.41 (W) x 1.26 (H) x 2.29 (D) inches

Weight: Approx. 2.9 oz



#### Remarks:

A-CWJ-TX & A-CWJ-RX are designed to be used with SSL-JVC50 battery only.

#### Other adapters and compatible batteries:

- A-CWS-TX/A-CWS-RX battery adapters : (Sony) NP-F550~NP-F970

