

TA-PV2USB

V-Mount Adaptor with USB and D-Tap Power

Instruction Manual

Thank you for choosing the TA-PV2USB. Designed to deliver reliable USB power, the TA-PV2USB can charge and power tablets, smart phones, remotes, wireless video transmitters (CW -1), and more. TA-PV2USB attaches directly to the IDX A-CP(A) universal mounting plate, or other 3rd party manufactured mounting plates and shoulder mounts. Please check which fixing positions are required for 3rd party plates and use the appropriate location holes. The TA-PV2USB incorporates an integral IDX V-Mount plate allowing direct mounting of any IDX EN-DURA battery. The TA-PV2USB has a D-Tap DC-out connector that supplies power directly from the battery allowing the use of professional monitors, on-board camera lights or other accessories. Please note, this is an unregulated output.

Specifications

Dimensions: 82.5(w) x 142(h) x 12(d) mm
Weight: 210g approx.
USB output voltage: 5V / 1A
D-Tap output voltage: 12~17V (Unregulated)
Maximum output for D-Tap: 50W
Included accessories: (4) M3 x 8 screws

General Notes & Safety

- Do not attempt to open or modify this unit. All work should be carried out by IDX authorised service personnel only.
- Do not attach the TA-PV2USB to any non-compatible video camera or equipment as it may cause defect, damage or other incidents. Please read this Instruction Manual carefully before use.
- When connecting a battery or adaptor to the TA-PV2USB, be sure to connect firmly. If it is not attached properly, it may result in loss or damage to the unit or even injury to the user.
- Do not expose to, use or place the unit in direct sunlight, extreme dust or other hazardous environments.
- A short between the plus (+) and minus (-) charge pins may cause fire, electrical shock or other incidents.
- Stop using immediately in case of abnormal smell, leak, color change or deformity during use.
- If you need any inspection or repairs, please contact your local IDX dealer or IDX office.

11262013



IDX System Technology, Inc.
19001 Harbortgate Way, Suite 105 Torrance, CA 90501
Tel: +1-310-328-2850
Fax: +1-310-328-8202
Email: idx.usa@idx.tv

TA-PV2USB

V-Mount Adaptor with USB and D-Tap Power

Instruction Manual

Thank you for choosing the TA-PV2USB. Designed to deliver reliable USB power, the TA-PV2USB can charge and power tablets, smart phones, remotes, wireless video transmitters (CW -1), and more. TA-PV2USB attaches directly to the IDX A-CP(A) universal mounting plate, or other 3rd party manufactured mounting plates and shoulder mounts. Please check which fixing positions are required for 3rd party plates and use the appropriate location holes. The TA-PV2USB incorporates an integral IDX V-Mount plate allowing direct mounting of any IDX EN-DURA battery. The TA-PV2USB has a D-Tap DC-out connector that supplies power directly from the battery allowing the use of professional monitors, on-board camera lights or other accessories. Please note, this is an unregulated output.

Specifications

Dimensions: 82.5(w) x 142(h) x 12(d) mm
Weight: 210g approx.
USB output voltage: 5V / 1A
D-Tap output voltage: 12~17V (Unregulated)
Maximum output for D-Tap: 50W
Included accessories: (4) M3 x 8 screws

General Notes & Safety

- Do not attempt to open or modify this unit. All work should be carried out by IDX authorised service personnel only.
- Do not attach the TA-PV2USB to any non-compatible video camera or equipment as it may cause defect, damage or other incidents. Please read this Instruction Manual carefully before use.
- When connecting a battery or adaptor to the TA-PV2USB, be sure to connect firmly. If it is not attached properly, it may result in loss or damage to the unit or even injury to the user.
- Do not expose to, use or place the unit in direct sunlight, extreme dust or other hazardous environments.
- A short between the plus (+) and minus (-) charge pins may cause fire, electrical shock or other incidents.
- Stop using immediately in case of abnormal smell, leak, color change or deformity during use.
- If you need any inspection or repairs, please contact your local IDX dealer or IDX office.

11262013



IDX System Technology, Inc.
19001 Harbortgate Way, Suite 105 Torrance, CA 90501
Tel: +1-310-328-2850
Fax: +1-310-328-8202
Email: idx.usa@idx.tv