



								
		CUE-D75	E-HL9	CUE-D95/ DUO-95 / DUO-C95	E-HL10DS	ELITE	CUE-D150/ DUO-150	DUO-C190
		73Wh	87Wh	91Wh	96Wh	136Wh	146Wh	185Wh
VL-PVC1	1ch	270	340	360	380	520	600	780
VL-2X	1ch	180	190	210	220	290	300	375
	2ch	360	380	420	440	580	600	750
VL-2PLUS	1ch	180	200	210	220	290	300	420
	2ch	360	400	420	440	580	600	840
VL-2SPLUS	1ch	140	130	145	145	185	195	250
	2ch	140	145	160	165	225	235	290
VL-4S VL-4Si VAL-4Si	1ch-3ch	155	155	175	180	240	255	305
	4ch	180	190	210	230	290	300	360

Note: Charge times displayed in minutes

All ENDURA V-Mount Batteries are compatible with ENDURA Chargers
 All ENDURA V-Mount chargers are worldwide compatible with input voltages ranging from AC100-240V

IDX System Technology
 19001 Harborgate Way Suite 105
 Torrance CA, 90501
 Telephone: (310) 328-2850

IDX Technology, Europe
 Unit 9 Langley Park, Westside Dr.
 Slough SL3 6AD, UK
 Telephone: +44 1753 547692

